




Bids and Awards Committee

Republic of the Philippines
 Professional Regulation Commission
 P. Paredes St., Sampaloc, Metro Manila
 Tel.Fax: 310-0037 / email:prcbac2013@gmail.com



ARISTOGERSON T. GISMUNDO
 Chairman

ARJAY R. ROSALES
 Vice-Chairman

MARIA LIZA M. HERNANDEZ
 Member

HENRIETTA P. NARVAEZ
 Member

WILMA T. UNANA
 Member

ALFONSO C. VILORIA
 Provisional Member, Non-IT Projects

GREGORIO B. DELORO
 Provisional Member, IT Projects

SECRETARIAT:

KAREN M. MAGSALIN
 Secretary

VICTOR RICO P. LOPEZ
 Member

MARGIERY D. DULIN
 Member

GLENN I. PAJARON
 Member

CHRISTOPHER A. MAYO
 Member

LIEZEL F. BURAGA
 Member

Section VII. Technical Specifications

Items	Description	Quantity	
1	BANDWIDTH MANAGER, HARDWARE	1	
	Bandwidth Manager Appliance		
	1.1. Link speed w/ shaping		500Mbps
	1.2. IP Flows (TCP) 3		350K
	1.3. IP Flows (UDP)		200K
	1.4. Classes		5K
	1.5. Dynamic Partitions		10K
	1.6. Static Partitions		5K
	1.7. Shaping Policies		5K
	1.8. Max Matching Rules		10K
	1.9. Matching Rules per Class		1K
	1.10. IP Hosts		350K
	1.11. Max AD Groups		250
	1.12. Available Slots		1 Full Height/ 1 Half Height
	1.13. Network I/O Modules (with bypass capacity)		4 x 10/100/1000Base-T
			4 x 1000Base-F, SX4
			4 x 1000Base-F, LX4
			2 x 10GBase-T
			2 x 10GBase-F, LR
	1.14. Onboard ports		2 x 1GbE Copper, Bypass
			1 x 1GbE Copper Management Port
1.15. Physical Dimension (LxWxH)	643x485.4x42.9 (chassis x/ extension)		
1.16. Weight	Approx. 12.8kg +/- 5%		
1.17. AC Power	Includes one power supply		
	100-127VAC@8A, 200-240VAC@4A, 47-63Hz		
1.18. Total Output Power	450 watts		
1.19. Thermal Rating	Typical: 1086BTU/Hr, Max: 1381 BTU/Hr		
1.20. Optional DC Power	Input Voltage range: 40.5V – 57V		
	Input Max Current: 22A		
	Total Output Power: 770W		
1.21. 1 Year End Customer Support, Level 1->3 Software Support & Same Day Shipment Hardware Support		1	

